



Continuum Simulations of Water Flow in Carbon Nanotube Membranes

Walther, Jens Honore; Popadic, A. ; Koumoutsakos, P.; Praprotnik, M.

Publication date:
2014

[Link back to DTU Orbit](#)

Citation (APA):

Walther, J. H., Popadic, A., Koumoutsakos, P., & Praprotnik, M. (2014). *Continuum Simulations of Water Flow in Carbon Nanotube Membranes*. Abstract from 67th Annual Meeting of the APS Division of Fluid Dynamics, San Francisco, CA, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Continuum Simulations of Water Flow in Carbon Nanotube Membranes J. H. WALTHER, Technical University of Denmark, Denmark, A. POPADIC, National Institute of Chemistry, Ljubljana, Slovenia, P. KOUMOUTSAKOS, ETH Zurich, Switzerland, M. PRAPROTNIK, National Institute of Chemistry, Ljubljana, Slovenia — We propose the use of the Navier-Stokes equations subject to partial-slip boundary conditions to simulate water flows in Carbon NanoTube (CNT) membranes. The finite volume discretisations of the Navier-Stokes equations are combined with slip lengths extracted from Molecular Dynamics (MD) simulations to predict the pressure losses at the CNT entrance as well as the enhancement of the flow rate in the CNT. The flow quantities calculated from the present hybrid approach are in excellent agreement with pure MD results while they are obtained at a fraction of the computational cost. The method enables simulations of system sizes and times well beyond the present capabilities of MD simulations. Our simulations provide an asymptotic flow rate enhancement and indicate that the pressure losses at the CNT ends can be reduced by reducing their curvature. More importantly, our results suggest that flows at nanoscale channels can be described by continuum solvers with proper boundary conditions that reflect the molecular interactions of the liquid with the walls of the nanochannel.

☒
☐Prefer Oral Session
Prefer Poster SessionJ. H. WALTHER
jhw@mek.dtu.dk
Technical University of Denmark